

Aktivna skretnica XO-300 OMNITRONIC



Ocjena: Neocjenjeno

Cijena

[Postavi pitanje vezano za ovaj proizvod](#)

Opis

Power supply: 230 V AC, 50 Hz

Power consumption: 20 W

Operation modes: 3-way stereo

Inputs: XLR, electronically balanced/unbalanced

Impedance: Balanced >50 kohms, unbalanced >25 kohms

Max. input level: +22 dBu typical, balanced or unbalanced

Outputs: XLR, electronically balanced/unbalanced

Impedance: Balanced 200 ohms, unbalanced 100 ohms

Max. output level: >+21 dBu balanced/unbalanced into 2 kohms or greater

S/N ratio: >100 dB

THD: 0.05%

Crosstalk: >80 dB, -3 dB

Crossover frequency low/mid: 80 Hz - 920 kHz

Procesori zvuka: Aktivna skretnica X0-300 OMNITRONIC

Crossover frequency mid/high: 800 Hz - 9.2 kHz
Filter type: Linkwitz-Riley, 24 dB/octave, state-variable
Phase invert: Low/mid output
Input gain: - ∞ to +6 dB
Output gain: - ∞ to +0 dB
Dimensions (WxDxH): 483 x 187 x 48 mm
Weight: 3.3 kg